



Shangrila 510S

Portable Ventilator

TECHNICAL
DATA

AEO MED
Reliable Quality Thoughtful Service

Shangrila 510S is a universally used model. Not only for emergency ventilation, but also it is suitable for ideal transport ventilation. The circumstances include on-site emergency treatment, pre-hospital transport, inter-hospital transport, and even intra-hospital transport.



Patient Type

Adult, Child, Infant (>3.5 kg)

Ventilation Modes

A/C-V with Sigh	A/C-P
SIMV-V	SIMV-P
SPONT/PSV	CPAP
MANUAL	

Enhancements

Apnea back-up ventilation	Manual breath
Alarm silence	

Parameter Setting

Tidal volume (Vt)	0-2000 mL
Pinsp	5-50 cmH ₂ O
Psupp	0-50 cmH ₂ O
CPAP (NIV)	0-30 cmH ₂ O
PEEP	0-30 cmH ₂ O
Pressure trigger	-20-0 cmH ₂ O
Flow trigger	2-30 L/min
Frequency (f)	1-120 bpm (A/C) 1-40 bpm (SIMV)
I:E ratio	4:1-1:10
Pause time (T _{pause})	0-5 s
O ₂ concentration	40-100 %
Inspiration flow	Max. 90 L/min

Monitoring Data

MV	VT	Frequency (f)
FiO ₂	Ppeak	PEEP

Waveform Display

P-T	F-T
-----	-----

Alarm Setting

High MV	OFF, 1-25 L
Low MV	OFF, 0-24 L
High FiO ₂	OFF, 50-100 %
Low FiO ₂	OFF, 35-99 %
High Paw	6-80 cmH ₂ O
Low Paw	0-40 cmH ₂ O
AC power failure	Gas supply down
O ₂ deficiency	MV high
Low battery	No VT
Apnea	CP high

Language

Chinese	English
Spanish	Italian
Turkish	Other languages

Environmental Requirements

Temperature

Operating condition	-18-50 °C
Storage condition	-20-60 °C

Relative humidity

Operating condition	15-95 %
Storage condition	10-95 %

Barometric pressure

Operating condition	70-110 KPa
Storage condition	50-110 KPa

Electrical

AC voltage	100-240 V, 50/60 Hz
DC voltage	12 V
One battery run time	Minimum 4.5 hours
Two batteries run time	Minimum 10 hours

Gas Supply

Supply pressure (O2)	250-600 kPa
Flow	Max. 180 L/min

Physical Specifications

Total Weight	8 kg
Dimension (H*W*D):	168* 156 *300 mm
LCD screen	5" TFT
Communication Ports	RS232